



CERTIFICATE

No.

PR-1993/007

APPLUS + CERTIFIED PRODUCT

LGAi Technological Center, S.A. (APPLUS) certifies that the product:

SAFES

FAMILY: **S800 LIGHT**. GRADE IV (See technical annex)

Produced by:

FERRIMAX, S.A.

C/ PROGRÉS, 2 - P.I. DE CAN BALIARDA
08105 SANT FOST DE CAMPSENTELLES (BARCELONA)

Is in accordance with the standard:

UNE-EN 1143-1:2019 (GRADE IV) SECURE STORAGE UNITS. REQUIREMENTS, CLASSIFICATION AND METHODS OF TEST FOR RESISTANCE TO BURGLARY. PART 1: SAFES, ATM SAFES, STRONGROOM DOORS AND STRONGROOMS

These standards are included in the scope of Order INT/317/2011, of February 1, published in BOE number 42 dated February 18, 2011 (Sec. I, P. 18333) and modified by Order INT/1504/2013 of 30 July.

The entity has performed the product initial tests and an initial assessment of the production process. Periodically, the entity does follow-up tests and assessment of the production process.

This certificate is valid until 4th February 2025, provided that the conditions set out in the contract are fulfilled.

Bellaterra, 4th February 2022


Applus⁺
LGAi Technological Center, S.A.

Xavier Ruiz Peña
Managing Director, Product Conformity B.U.



This document is not valid without its technical annex; whose number coincides with that of the certificate.

You can check the validity of this certificate on our website: www.appluslaboratories.com/certified_products

PR-1993/007

Nr.	MODELS	GRADE 1143-1	EXTERNAL DIMENSIONS (mm)	WEIGHT (kg)
1	CF-810L	IV	625 x 535 x 470	300
2	CF-812L	IV	870 x 530 x 500	400
3	CF-815L	IV	1024 x 599 x 577	550
4	CF-816L	IV	1000 x 665 x 495	480
5	CF-816LF	IV	1000 x 665 x 670	500
6	CF-817L	IV	1145 x 645 x 580	650
7	CF-820L	IV	1270 x 695 x 590	750
8	CF-830L	IV	1440 x 760 x 570	850
9	CF-850L	IV	1620 x 800 x 640	1050
10	CF-880L	IV	1820 x 1400 x 800	1900
11	FD-812L	IV	870 x 530 x 500	415
12	FD-815L	IV	1024 x 599 x 577	565
13	FD-816L	IV	1000 x 665 x 495	500
14	FD-816LF	IV	1000 x 665 x 670	515
15	FD-817L	IV	1145 x 645 x 580	670
16	FD-820L	IV	1270 x 695 x 590	770
17	FD-830L	IV	1440 x 760 x 570	875
18	FD-850L	IV	1620 x 800 x 640	1075
19	FD-880L	IV	1820 x 1400 x 800	2000